

StaticWorx TriboGround Dissipative Buffing
Solution for Raised Access Floors

PRODUCT DESCRIPTION

prevent the build-up of static electricity on standard access floor panels. Responds well to spray buffing and dry burnishing to restore the electrical properties and luster with minimal effort. TriboGround provides static dissipative properties and a high shine to old, dull access flooring panels.

- Reduces static on any surface.
- High viscosity properties prevent seepage between panels
- Provides high shine on access floor panels
- For use on HPL, vinyl, VCT & static dissipative surfaces

APPLICATION & MAINTENANCE

Remove loose dirt and soil by sweeping or vacuuming. For best results the area to be buffed should be damp mopped with StaticWorx TriboClean. Apply a three-to-four inch line of TriboGuard to the floor and distribute it evenly over a white or beige high speed polishing pad. Using a buffing machine, work small areas at a time. Following buffing, sweep up any residual dirt or soil discharged in the buffing process.

SAFETY INFORMATION

Health	1
Flammability	1
Reactivity	0
Personal Protection	B

CAUTION: May cause eye and skin irritation. If eye contact occurs, flush with plenty of water and get immediate medical attention. For skin contact, wipe off area with a towel and rinse with plenty of water. If swallowed, induce vomiting and get immediate medical attention. Read Material Safety Data Sheet thoroughly before using.

SPECIFICATIONS

Nonvolatile Solids	3 - 4%
Total Active	12%
pH	7.8 - 8.5
Color	White Emulsion
Weight per Gallon	8.1
Stability	1 year minimum at room Temperature
Freeze/Thaw Stability	3 cycles
Water Resistance	Excellent
Coverage per 4" Application	500 - 800 ft ²